

# PJD2121

**ULTRA-PORTABLE PROJECTOR**  
WITH BrilliantColor™ TECHNOLOGY

## Our Best In Portability

The new ViewSonic® PJD2121 compact portable projector leaves nothing behind but the weight. Brilliant images, produced at 400 lumens with a contrast ratio of 1800:1, ensure your presentation will always shine. Texas Instruments' BrilliantColor™ technology creates pictures true to life. Using multiple picture modes you can create a presentation that will be entertaining and memorable. It supports both 720p and 1080i HD formats. The bottom load lamp and filter-less design provide for easy maintenance and low total cost of ownership. This easy to pack and go device is light weight – just over 2 pounds – and is ready to perform anywhere you take it.



### PERFORMANCE YOU TAKE WITH YOU

- > **Compact portable projector**  
With a small profile, only 8" x 4 ¾" x 2 ½", this projector is perfect for people on the go.
- > **Super light weight for ultimate mobility**  
At just over 2 pounds this projector can effortlessly be carried in briefcase or travel bag.
- > **BrilliantColor™ technology**  
Latest BrilliantColor™ technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enriches the yellow color performance that is key to accurate and vivid color reproduction.
- > **Short throw displays a 60" crisp image from just 4 feet**  
Just right for small spaces or small groups.
- > **ViewMatch™ quick key for optimal color**  
Make adjustments from the remote control for quick and accurate color corrections.
- > **Off-to-Go feature**  
The direct off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects the lamp from sudden power blackouts.
- > **Supports HD signals including 720p and 1080i**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic®**  
See the difference® 

# PJD2121

## ULTRA-PORTABLE PROJECTOR WITH BrilliantColor™ TECHNOLOGY



### Optional Accessories

- Replacement lamp..... RLC-052
- Extended Express Exchange® ..... PRJ-EE-03-03
- Wireless G Presentation Gateway .... WPG-350



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*See ViewSonic.com for full details. †Adapter may be required. Analog adapter available from ViewSonic. DLP® and the DLP logo are registered trademarks of Texas Instruments and BrilliantColor™ is a trademark of Texas Instruments. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved. [14467-00B-07/09] PJD2121-1

<b>PROJECTOR</b>	Type	0.55" Digital Micromirror Device (DLP®)
	Pixel Format	800x600 SGVA
	Lens	Manual focus
	Zoom Factor	Fixed optical
	Keystone	Vertical ± 30°
<b>DISPLAY</b>	Size	35"–150" (diagonally)
	Throw Distance	28"–120"
	Throw Ratio	1.0:1
	Lamp	50W, 2,000 hrs. normal
	Brightness (max)	400 ANSI lumens
	Contrast Ratio	1,800:1
<b>INPUT SIGNAL</b>	Computer and Video	RGB analog, NTSC, HDTV (480i, 480p, 576i, 576p, 720p, 1080i)
	Frequency	F <sub>H</sub> :15–82kHz; F <sub>V</sub> :50–85Hz
	<b>COMPATIBILITY</b>	PC
	Mac®†	Analog: up to SXGA
<b>CONNECTOR</b>	RGB (input)	15-pin HD, D-sub
	Component Video (input)	RCA jack x1 set
<b>POWER</b>	Voltage	90–264vac, 50/60Hz (auto switching)
	Consumption	90W (max)
<b>CONTROLS</b>	Basic	Standby/on, input, menu
	OnView®	Display mode, brightness, contrast, keystone, aspect ratio, blank screen, color temperature, user color, video (sharpness, saturation, tint), display (phase, tracking, H. position, V. position), advance (pan and scan, magnify, auto source, select, lamp hours, lamp reset, factory reset)
<b>OPERATING</b>	Temperature	32–104°F (0–40°C)
<b>CONDITIONS</b>	Humidity	10–85% (non-condensing)
	Altitude	0–10,000 ft.
<b>NOISE LEVELS</b>	Normal	31 dB (typ)
<b>DIMENSIONS</b>	Physical (W x H x D)	8.1" x 4.7" x 2.6" ( 205mm x 120mm x 65mm)
<b>WEIGHT</b>	Net	2.16 lb. (0.98 kgs)
	Gross	5.5 lb. (2.5 kgs)
<b>REGULATIONS</b>		UL/cUL, FCC-B, CE, CB, CCC, NOM, ICES 003, IRAM, TUV/GS, GOST-R, HYGIENIC, SASO, UKrSEPRO, RoHS
<b>RECYCLE/DISPOSAL</b>		The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.
<b>PACKAGE CONTENTS</b>		Projector, power cable with adapter, VGA cable, remote control, soft case, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)
<b>WARRANTY</b>		3-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1-year free Express Exchange® service*

**ViewSonic®**  
See the difference® 

For more product information, visit us on the web at ViewSonic.com