



## Epson EB-4955WU

### The Ultimate Projection Solution For Any Meeting Space

3 x Brighter Colours and reliable performance\* – 3LCD, 3-Chip Technology.  
Look for both high colour brightness and high white brightness

Crisp Clear Images – Featuring WUXGA resolution

Lens Shift – Align images easily with horizontal & vertical lens shift

Versatile connectivity – Easily integrate with any system with HDMI  
& DisplayPort

Convenient Remote Management – Remotely monitor & control presentations

Epson iProjection™ – Wirelessly display and control content from your  
iPhone®, iPad®, iPod touch® and Android™ devices

Arc & Point Correction – Fine tune image geometry to perfection

Passive 3D – For stacked 3D applications using polarised passive glasses

# Epson EB-4955WU



## Product Specifications

|  |   |
|--|---|
| <b>PRODUCT NAME</b>                        | Epson EB-4955WU   |
| <b>PRODUCT CODE</b>                        | V11H563153  |
| <b>WHAT'S IN THE BOX</b>                   | EB-4955WU Projector, 3m Power Cable, 1.8m Computer Cable, Remote Control, 2 x AA Batteries, HDMI Cable Clamp, Cable Cover, Manual, Projection Software CDROM. |
| <b>TECHNOLOGY</b>                          |   |
| <b>Projection System</b>                   | RGB liquid crystal shutter projection system  |
| <b>LCD Panel</b>                           | 0.76-inch wide panel with MLA   |
| <b>OPTICAL</b>                             |   |
| <b>Zoom</b>                                | 1 - 1.8 (Optical)   |
| <b>Screen Size</b>                         | 50" to 300" [1.35m to 8.36m] (Zoom: Wide)<br>50" to 300" [2.47m to 15.01m] (Zoom: Tele)   |
| <b>Projection Distance</b>                 | 100" screen 2.75m - 4.98m   |
| <b>Throw Ratio</b>                         | 1.26 (Zoom: Wide), 2.30 (Zoom: Tele)  |
| <b>Projection Lens F Number</b>            | 1.65-2.55   |
| <b>Projection Lens Focal Length</b>        | 21.28mm - 37.94mm   |
| <b>Focus Method</b>                        | Manual  |
| <b>IMAGE</b>                               |   |
| <b>Colour Light Output</b>                 | 4,500 Lumens  |
| <b>White Light Output</b>                  | 4,500 Lumens  |
| <b>Resolution</b>                          | WUXGA   |
| <b>Native Aspect Ratio</b>                 | 16:10   |
| <b>Contrast Ratio</b>                      | 5,000:1   |
| <b>Lamp Hours</b>                          | 4000 hours (Normal)<br>5000 hours (ECO)   |
| <b>Lamp Type</b>                           | 280 W UHE   |
| <b>Keystone Correction (With Std Lens)</b> | Vertical: -30 to +30 degrees<br>Horizontal: -30 to +30 degrees  |
| <b>Lens Shift</b>                          | Vertical: -50% to +50%<br>Horizontal: -10% to +10%  |
| <b>Tilt Angle</b>                          | -2.50 to 10 degrees   |

\* Compared to leading 1-chip DLP business and education projectors based on NPD data, July 2011 through June 2012. Colour brightness (colour light output) measured in accordance with IDMS 15.4. Colour brightness will vary depending on usage conditions.

|                                     |   |
|-------------------------------------|---|
| <b>CONNECTIVITY</b>                 |   |
| <b>Input: Video</b>                 | 1 x RCA (Yellow), 1 x S-Video, 1 x 5BNC   |
| <b>Input: Computer</b>              | 1 x D-sub 15-Pin (RGB)  |
| <b>Input: Digital</b>               | 1 x HDMI, 1 x DisplayPort   |
| <b>Input: Audio</b>                 | 3 x Stereo mini-jack, 1 x RCA (Red/White), 1 x HDMI, 1 x DisplayPort  |
| <b>Input: Control</b>               | 1 x RS232c, 1 x Stereo mini-jack (Remote)   |
| <b>Input: Network I/O</b>           | 1 x RJ45, 1 x USB Type A (for optional Wireless LAN unit)   |
| <b>Wireless Connectivity</b>        | Optional  |
| <b>Output: Video</b>                | 1 x Monitor Out (via D-sub 15-pin)  |
| <b>Output: Audio</b>                | 1 x Stereo mini-jack  |
| <b>Speaker Output</b>               | 10W   |
| <b>ADVANCED FEATURES</b>            |   |
| <b>EasyMP Network &amp; Control</b> | Yes   |
| <b>EasyMP Network Projection</b>    | Yes   |
| <b>Split Screen</b>                 | Yes   |
| <b>Edge Blending</b>                | -   |
| <b>Arc Correction</b>               | Yes   |
| <b>Frame Interpolation</b>          | -   |
| <b>360 Degrees Projection</b>       | -   |
| <b>Passive 3D Capable</b>           | Yes   |
| <b>Instant Off</b>                  | Yes   |
| <b>Direct Power On/Off</b>          | Yes   |
| <b>Security</b>                     | Kensington®-style lock provision<br>Padlock & Security cable hole<br>Wireless LAN Lock  |
| <b>Colour Modes</b>                 | Photo, Presentation, Theatre Dynamic, sRGB, Multi-Projection, DICOM SIM, 3D Presentation, 3D Theatre, 3D Dynamic, 3D Multi-Projection |
| <b>GENERAL</b>                      |   |
| <b>Dimensions D x W x H</b>         | 472 x 159 x 354 mm  |
| <b>Weight</b>                       | 6.6kg   |
| <b>Lamp Warranty</b>                | 1 Year or 750 Hours**   |
| <b>Projector Warranty</b>           | 3 Years   |
| <b>Power Consumption: Lamp on</b>   | 388W  |
| <b>Power Consumption: Standby</b>   | 0.47W   |
| <b>Noise Level</b>                  | Normal/Eco: 38/30 dB  |

\*\* Whichever comes first



## Better Products for a Better Future

Epson is the registered trademark of Seiko Epson Corporation. All other names and company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All print samples shown herein are simulations. Specifications are subject to change without notice.

**EPSON AUSTRALIA**  
3 Talavera Road  
North Ryde NSW 2113  
Tel: (02) 8899 3666  
[www.epson.com.au](http://www.epson.com.au)

**EPSON NEW ZEALAND**  
Level 2, 7-9 Fanshawe Street  
Auckland, 1010  
Tel: (09) 366 6855  
[www.epson.co.nz](http://www.epson.co.nz)

ABN 91 002 625 783  
06/13

**EPSON**  
EXCEED YOUR VISION