# PJ-LC7

HITACHI'S NEW PJ-LC7 HOME CINEMA PROJECTOR WILL MAKE YOU THINK AGAIN ABOUT THE WAY YOU ENJOY MOVIES AND TELEVISION AT HOME.

The PJ-LC7 is a stylish, compact and portable LCD projector ideally suited for use in the home. Easy to set up to watch movies, sports events or even to enjoy computer games on a bigger screen. It offers high quality performance at excellent value for money.

You can display a 50" diagonal image from only 1.8m away. The PJ-LC7 produces sharp images, high brightness and excellent colour reproduction.

- Tri-LCD Projector with 0.55" Panels
- SVGA resolution
- Brightness 1500 ANSI Lumens
- Projection Distance 1.8:1
- Electronic Zoom x 1.2
- Digital Vertical Keystone
- Video and Data Inputs
- Weight 2.25Kg
- Noise Level <33dB</li>



## PJ-LC7

## **Technical Specifications**

OPTICAL

LCD Panel 0.55" P-Si TFT x 3 with MI A Resolution 800 dots x 600 lines

F1.65 Fixed (f=20.4mm), x 1.2 Electronic Zoom, Manual Focus Lens

Lamp 165W UHB Lamp Life 2000 hours Brightness (Normal) 1500 ANSI Lumens 1200 ANSI Lumens (Whisper)

Contrast Ratio 400:1 (typ) 1.46~7.4m (60"@2.2m) Focus Distance 40-200" diagonal 8 Bits/colour, 16.7M colours Display Size Colour

COMPATIBILIT'

PAL (-BGDHI), SECAM, PAL-M, PAL-N, NTSC, NTSC4.43 Composite Video

SDTV: 525i (480i), 525p (480p), 625i (576i) HDTV: 750p (720p@60Hz), 1125i (1080i@50/60Hz)

IBM Compatible VGA, SVGA, XGA, (Smart Resizing), SXGA Capability, MAC 16" (PixelWorks Chip PW168)

Plug & Play

Frequency Range Horizontal: 15~91kHz, Vertical: 50~120Hz

FEATURES

Computer

Fixed 6:1 upward shift, Normal@8.4° projection angle Keystone Correction

Speakers

Other MENU: 17 Language: (English, French, German, Spanish, Italian,

Norwegian, Dutch, Japanese, Portuguese, Turkish, Traditional Chinese, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish), Freeze Function, Magnifying, Digital Gamma Correction, My Memory (4 settings), 2-3 pull down, Electrical V Keystone Correction, Auto Configuration (H-Size, Position), PIN Lock System

CONNECTORS

1 x Composite Video RCA Jack 1 x S-Video Mini-DIN 4-pin Video Input

Data Input 1 x 15-pin D-sub

1 x 9-pin D-sub for RS-232C (Serial) Control Audio Input 1 x Stereo Mini Jack

Power Supply 100~120/220~240V AC, 50/60 Hz, auto switching

Power Consumption 240W

PHYSICAL

Dimensions (W x H x D) 285 x 73 x 202mm (excluding feet and extrusions)

Weight 2.25Ka Noise Level <33dB

### MISCELLANEOUS

Lamp Indicator Light, Power Light, Ceiling Mount Image, Rear Projection Image, Magnify (4x), Easy/Advanced OSD Menu, Component/RGBHV on Data Input Port

#### ACCESSORIES SUPPLIED

Remote Control (No laser),

Power Cord

Batteries RGR Cable

Filter Cover for Ceiling Mount Use


Safety Instructions (15 languages)

Quick Guide (14 languages)

Uduk Gude (14 iniguages) User Manual (14 languages on CD: English, German, French, Italian, Spanish, Dutch, Norwegian, Portuguese, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish)


Replacement Lamp


DT000701



Screen Size	a	b (top)	c (bottom)
(Diagonal)			
40" (1.0m)	1.5m (57")	52.3cm (21")	8.7cm (3")
50" (1.3m)	1.8m (72")	65.3cm (26")	10.9cm (4")
60" (1.5m)	2.2m (87")	78.4cm (31")	13.1cm (5")
70" (1.6m)	2.6m (101")	91.4cm (36")	15.2cm (6")
80" (2.0m)	2.9m (116")	104.5cm (41")	17.4cm (7")
90" (2.3m)	3.3m (130")	117.6cm (46")	19.6cm (8")
100" (2.5m)	3.7m (145")	130.6cm (51")	21.8cm (9")
120" (3.0m)	4.4m (174")	156.8cm (62")	26.1cm (10")
150" (3.8m)	5.5m (218")	195.9cm (77")	32.7cm (13")
200" (5.1m)	7.4m (291")	261.3cm (103")	43.5cm (17")

## HITACHI Inspire the Next





HITACHI DIGITAL MEDIA Hitachi Europe Ltd Lower Cookham Road Maidenhead Berkshire SL6 8YA

Tel: 01628 585 000 Fax: 01628 585 500

The specification above and photography is for reference only and may be subject to change.