

ME301W

Professional Desktop Projector

Datasheet





Great performance with low TCO

Guaranteeing the perfect support for successful lectures and presentations, the compact multi-purpose ME301W projector delivers crisp images and natural colours to your classroom and meeting facility thanks to LCD technology and 3000 ANSI lumen brightness. Comprehensive connectivity and optional WiFi provide the utmost flexibility and time saving operation. The pre-installed MultiPresenter function enables simultaneous wireless presenting and sharing for up to 16 devices when the optional WiFi is chosen. Extended lamp and filter life are lowering both maintenance time and cost ensuring a smooth operation over 5 years*.

The ME301W is the perfect choice when considering replacing M Series WXGA LCD projectors. With the same footprint, lens position and throw angle it has never been easier to bring the latest technology to your classroom or meeting facility saving both time and money with no maintenance. With its downward compatibility for lamps of the M LCD series even your stock is a safe investment!

*at 8 hours operation a day, 200 days a year

Benefits

Large 1.7x optical zoom – for maximum flexibility.

Minimized cost of ownership – due to long lamp life and filter exchange intervals.

Versatile and mobile – compact and light-weight with HDMI and integrated 20W speaker.

Display content that demands attention – with WXGA resolution and superb brightness levels and colour ranges, your viewers will enjoy an outstanding visual experience.

Cost effective replacement – of existing NEC M LCD model installations to achieve better imaging for lectures and presentations without wall-mount adjustment.

Wide array of flexible application scenarios – thanks to multi-source conferencing and efficient split-screen operation supported by a wide future-ready range of digital connectivity.



Product Name	ME301W	
Product Group	Professional Desktop Projector	
Order Code	60004229	
lmage		
Projection Technology	3LCD Technology	
Native Resolution	1280 x 800 (WXGA)	
Aspect Ratio	16:10	
Contrast Ratio ¹	6000:1	
Brightness ¹	3000 High Bright / 2400 Normal / 1800 Eco ANSI Lumens	
Lamp	214 W AC (140 W AC Eco Mode)	
Lamp Life [hrs]	9000 Eco / 5000 Normal / 4000 High Bright Mode	
Lens	F= 1.7–2.1, f= 17.5–29 mm	
Keystone correction	+/- 30° manual horizontal / +/- 30° manual vertical	
Projection Angle [°]	10.7 - 11.4	
Projection Factor	1.3 – 2.2 : 1	
Projection Distance [m]	0.7 – 14.6	
Screen Size (diagonal) [cm] / jinch]	Maximum: 762 / 300"; Minimum: 76 / 30"	
Zoom	Manual	
Focus Adjustment	Manual	
Supported Resolutions	1920 x 1200 (WUXGA); 1920 x 1080 (HDTV 1080p/i); 1680 x 1050 (WSXGA+); 1600 x 1200 (UXGA); 1600 x 900 (WXGA++); 1440 x 900 (WXGA+); 1400 x 1050 (SXGA+); 1280 x 1024 (MAC 23"); 1280 x 1024 (SXGA); 1280 x 800 (WXGA); 1280 x 768 (WXGA); 1280 x 720 (HDTV 720p); 1152 x 870 (MAC 21"); 1024 x 768 (XGA); 1024 x 768 (MAC 19"); 832 x 624 (MAC 16"); 800 x 600 (SVGA); 720 x 576 (SDTV 480p/i); 720 x 480 (480p); 720 x 480 (SDTV 480i); 640 x 480 (VGA); 640 x 480 (MAC 13")	
Frequency	Horizontal: 15–100 kHz (RGB: 24 kHz– 100 kHz); Vertical: 50 – 120 Hz	
Connectivity		
RGB (analog)	Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin	
Digital	Input: 2 x HDMI™ (Deep Color, Lip sync)	
Video	Input: 1 x RCA	
Audio	Input: 2 x 3.5 mm Stereo Mini Jack; 2 x RCA Stereo Output: 1 x 3.5 mm Stereo Mini Jack	
Control	Input: 1 x D-Sub 9 pin (RS-232) (male)	
_AN	1 x RJ45; Optional WLAN	
JSB	1 x Type A (USB 2.0 high speed); 1 x Type B	
Video Signals	NTSC; PAL; PAL60; SECAM	
Remote Control		
Remote Control	Aspect Ratio; Audio Control; Auto Adjust; AV Mute; Digital Zoom; Freeze; Help Eco Mode; ID set; Optional Presentation and Mouse Control; Picture Adjust; Picture Mode; Source Select	

Professional	Desktop	Projector -	ME301W	(2)	4)
--------------	---------	-------------	--------	-----	---	---

 $230 \; (Normal) \; / \; 193 \; (Eco) \; / \; 2.3 \; (Network \; Stand-by) \; / \; 0.45 \; (Stand-by); \; 274 \; (High \; Bright)$

100-240 V AC; 50 - 60 Hz

Power Supply

Mechanical

Power Consumption [W]

339 x 108.5 x 259 (without lens and feet) 2.9 29 / 35 (Eco / Normal)				
29 / 35 (Eco / Normal)				
5 to 40				
20 to 80				
-10 to 50				
20 to 80				
EAC; ErP; RoHS; WEEE				
1 x 20 (mono)				
Auto Eco Mode; Auto Power ON/OFF; Carbon Savings Meter; Colour Management; Content Transmission				
via Network; Crestron RoomView; DICOM Simulation; Direct Power-Off Function; High Altitude Mode;				
Kensington security slot; Keypad Lock; Keystone Correction (H=±30°, V=±30°); Lens Cover; Magnify;				
NaViSet Administrator 2; Off-Timer; Optional User Logo; Optional WLAN; OSD with 29 languages; Password				
Security System; Quick On/Off; RS-232 Control; Security Bar; USB Display; USB Viewer for JPEG; Virtual				
Remote for direct PC control; Wall Colour Correction				
75 % AV mute function; Auto ECO Mode; ECO scheduler; Green one touch ECO and AV mute button;				
Intelligent Power Management; Longer lamp life; Reduced power consumption. Only 0.45W stand-by; Software scheduling				
100% recyclable packaging; Downloadable manuals; ECO packaging				
ErP compliant; RoHs compliant; WEEE				
3 years pan-European service				
6 months, max. 1000 hrs				
IR Remote Control (RD-469E); Mini D-SUB Signal Cable (1.8 m); Quick Setup Guide; Security Sticker; Users				
Manual on CD-ROM; Utility software				
DisplayNote; Lamp (NP43LP, NP16LP); MultiPresenter Stick; Universal Ceiling Mounts (PJ01UCM); Wireless				
LAN module NP05LM2 (Europe), NP05LM4 (Russia)				

¹ Compliance with ISO21118-2012





This document is @ 2017 NEC Display Solutions Europe GmbH.

pecifications are subject t	e names are brand name Errors and omissions ar	marks of the