

EK-620U

6,500 lumens bright and a 100,000:1 contrast ratio.

Lampless Laser Technology.

1-chip DLP® technology.

3 Digital Inputs including HDBaseT.

Native WUXGA resolution. Compatible with inputs up-to UXGA and WUXGA. Supports analog and digital video input in all color standards up-to 1080p.

Displays both 4:3 and 16:9 aspect ratios. Supports most HDTV resolutions.

Flexible Installation up to 360°

Wired network monitoring and control.

Wifi available with optional USB Dongle.

Horiz. Vert. and Corner Keystone Correction.


Pin Cushion and Barrel image correction. Built-in Picture in Picture and Picture by Picture.

Security bar. Kensington® MicroSaver® security slot. PIN lock.

*3 year projector warranty.



6,500 Lumens / WUXGA / 1-chip DLP® "Large Venue" Series Projector Laser (Blue) + Phospher



Included Accessories:

Quick Start Guide, VGA Computer Input Cable (Dsub15 to Dsub15), 6.0 ft (1.8 m) Detachable Power Cord Lens Cover, Remote Control (with 2 AAA Batteries).

Optional Accessories:

ATA-Style Case with Wheels and Telescoping Handle, Ceiling Mount, Ceiling Post and Plate.

Specifications: Model EK-620U

6,500 ANSI Lumens **Brightness Contrast Ratio** 100 000:1 Resolution and Aspect Ratio WUXGA (1920 x 1200), 16:10 Color Reproduction 10 bit **Projection Light Source** Laser (Blue) + Phospher **Total Pixels** 2,304,000 (1920 x 1200) x 1 0.67" DMD™ DLP® chip x 1 **Imaging System Scanning Frequency** Auto: H Sync. 15.734-91.146 kHz, V Sync. 24-120 Hz **Pixel Clock** 162 MHz Optional Lenses Available - See lens chart on website Lens Lens Specs Optional Lenses Available - See lens chart on website Lens Ratios Optional Lenses Available - See lens chart on website Image Diagonal 50-300 in (127-762 cm) Image Width 3.3-20 ft (1.0-6.1 m) Throw Distance 5.9-48.8 ft (1.8-14.9 m) **Maximum Pitch** up-to 360° Digital: up-to 20° Up or Down **Vertical Keystone Correction** Digital: up-to 20° Left or Right **Horizontal Keystone Correction** Normal, Reversed, Inverted Image Orientation Local Control / Power Management Full Function / Auto Shutdown Remote Control Wireless / Wired x 1 Remote Control / RS-232 Control MiniStereo x 1 / Dsub9 x 1 LAN Port RJ45 x 1 up-to 1600x1200 (4:3), 1920x1200 (16:10) **Computer Input in Pixels** Analog 4x3 Inputs UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC **Analog Wide Inputs** WUXGA, WSXGA+, WXGA+, WXGA Digital 4x3 Inputs UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC **Digital Wide Inputs** WUXGA, WSXGA+, WXGA+, WXGA Video Input Analog 480i/p, 576i/p 480p, 575p, 720p, 1080i/p Video Input Digital

Image Signal Resizing Image Signal Inputs Computer 1 Digital Video (w/ HDCP) Digital Video (w/ HDCP) **HDBaseT** USB Type A - Wifi Dongle Mini USB - Service Outputs Computer Digital Video (w/ HDCP) 3D Sync Out Fan Noise (Normal / Eco) Cabinet Size (HxWxD) - excluding legs Weight (without lens) Packaged Size (HxWxD) Packaged Weight **Operating Temperature Electrical Safety Compliance Electromagnetic Compatibility Power Requirements Power Consumption** Heat **Security Facilities** UPC Limited Warranty: to the original end use customer only

Smart Scaling Technology Dsub15 x 1 HDMI x 1 DVI-D x 1 RJ45 x 1 Type A x 1 Mini USB x 1 Dsub15 x 1 HDMI x 1 Mini Din 3 x 1 35 / 32 dB 7.1 x 19.0 x 20.0 in (18.0 x 48.1 x 50.8cm) 51.5 lb (23.4 kg) 15.5 x 24.7 x 23.4 in (39.3 x 62.7 x 59.5 cm) 62.8 lb (28.5 kg) 41-95°F (5-35°C) IEC / ÙL / cUL FCC Class A, CE Mark 100-240V AC, 50/60 Hz 0.5 W in Eco Standby mode, up-to 765W up-to 2,608.7 BTU/hr Security Bar, Kensington® Security Slot 4571194678574 *3 years / 6000 hours

Projector

*(whichever occurs first)

Caution! Laser Radiation - Do not stare into beam. Max. Output: 1m Wave Length: 640 ~ 660 nm. Class II Laser Product Lamp contains Mercury. Do not put in trash. Dispose of as Hazardous Waste, according to Local, State or Federal Laws. EIKI® is a registered trademark of Eiki International Inc. Kensington is a registered trademark of ACCO Brands Corporation.

