



XJ-UT351W / WN

ULTRA SHORT THROW SERIES

LampFree. MercuryFree. StressFree.

Casio's Ultra Short Throw LampFree® projectors incorporate Laser & LED Technology to produce images of impressive brightness. They have a long lasting lifespan of up to 20,000 hours with reduced electricity consumption and no lamps or filters to replace.

With their Ultra-Short Throw lens, the XJUT351W and XJ-UT351WN can project brilliant, crisp, shadow-free images of up to 110" diagonal with a full assortment of connectivity and features. The built-in short throw lens and advanced mirror system provides an extremely close throw ratio (0.28:1) and projects an 80" image from just 1.5 feet away.

Key Features

- 3500 Lumens
- Ultra Short Throw Ratio (.28:1)
- Dust Resistant Design
- Built-in 16W speaker
- Expanded input/output connectivity
- High Contrast Ratio of 20,000:1
- DLP® Technology

LampFree Features

- Laser & LED Hybrid Light Source
- Long Life, 20,000 hour estimated operating life
- No Lamp replacement required
- No Filters
- Less Down Time
- Low Power Consumption
- Mercury Free
- Quick On – (5 seconds to full brightness)
- Instant Off – no cool down required

XJ-UT351WN Only

- RJ-45 Wired LAN
- Wireless Capability
- Optional Wireless Adaptor (YW-40) Available

| CASIO Projector Specifications | XJ-UT351W | XJ-UT351WN |
|----------------------------------|------------------------------------|---|
| Native Resolution | | WXGA |
| Native Aspect Ratio | | 1280 x800 |
| Brightness | | 16:10 |
| Display Device | | 3500 lumens |
| Contrast Ratio | | 0.65" DLP® chip |
| Lens Type | | 20,000:1 |
| Lens Spec F/f | | Fixed Zoom/Manual Focus |
| Lens Offset | | Fixed lens F2.3/f4.2 |
| Light Source | | 70% |
| Projection Screen Size (Min-Max) | | Laser & LED (Up to 20,000 Hours) |
| Projection Range | | 50 to 110-inch diagonal |
| | 60-inch screen | 0.4 ft |
| | 100-inch screen | 1.3 ft |
| | Minimum | 0.2 ft |
| | Throw Ratio (60 inches) | 0.28:1 |
| Keystone Correction | | Vertical and Horizontal + or - 5° (Manual) |
| Color Reproduction | | Full color (1.07 billion colors) |
| Power Consumption | | — |
| | Operating (Default) Light Output 7 | 185W |
| | Operating (Minimum) Light Output 1 | 125W |
| | Operating (Bright) | 225W |
| | Standby (Remote Off/On) | 0.23 W/2.6 W |
| TERMINAL CONNECTIVITY | | |
| Maximum Signal Input | | WUXGA (1920 x 1200) |
| Analog input terminal | | mini D-Sub 15 pin x 2 |
| RGB/Component Video Input | | mini D-Sub 15 pin x 1 Also use as YCbCr/YpPr input— commercially available adapter required |
| HDMI Input | | HDMI Type A x 2 (480p-1080p) |
| USB Input | — | USB 2.0 Type A x 1 |
| Composite Video Input | | Video (RCA) x1, S Video x 1 |
| Audio Input | | RCA (R/L) x1, Stereo Mini x 2 |
| USB Power Supply | | DC 5V / 2A |
| Microphone Input | | 3.5 mm Mini |
| Built-in Memory | | — |
| Logo Transfer | | USB 1.1 Micro-B x 1 |
| Audio Output | | Stereo Mini x 1, Mini D-sub 15 pin x 1 |
| Monitor Output | | mini D-Sub 15 pin x 1 |
| Control (Serial) Terminal | | RS-232C (D sub 9 pin) x 1 Cross Cable (Null Modem) required |
| Built in Speaker | | 16W Monaural Speaker |
| LAN | — | RJ-45 x 1 |
| Wireless Capability | — | Optional Wireless LAN Adapter (YW-40) Available |
| OTHER INFORMATION | | |
| Operating Temperature | | 41° - 95° F |
| Operating Humidity | | 20% - 80% (non-condensation) |
| Remote Control Operating Range | | 16.4 ft. Max. |
| Kensington / Power On Password | | Yes |
| Product Dimension (W x D x H) | | — |
| | Excluding Projections | 16.5 x 13.1 x 6.0 inches |
| Weight | | 13.23lbs |
| Packing Information | | — |
| | Carton Dimensions | 20.9 x 16.2 x 10.2 inches |
| | Carton Weight | 19.4 lbs |
| Included Accessories | | Remote control, 6' RGB cable, 6' AC Power Cord |
| Mounting Screws | | M4 x 4 (not included) Insert depth (5-8 mm) |
| UPC Code | 889232800431 | 889232800448 |
| Manufactured in | | Japan |

Terminal Interface



XJ-UT351W



XJ-UT351WN

Designed and Manufactured by Casio in Japan
TAA Compliant

CASIO.

ProSelecta

View :: Compare :: Select - www.ProSelecta.com