PJ559D

LIGHT, BRIGHT AND PORTABLE PROJECTOR

with BrilliantColor™

High brightness, full-featured projector.

The ViewSonic® PJ559D DLP® projector features 2,700 lumens, native 1024x768 resolution, ultra-high 2000:1 contrast ratio and BrilliantColor™ technology for precise images in any lighting condition. This full-featured projector includes MULTIPLE INPUTS for connecting several display sources simultaneously, dual 5-watt speakers for complete multimedia presentations, VERTICAL KEYSTONE CORRECTION for easy image adjustment and DIRECT OFF FEATURE. Choose from whiteboard, blackboard or greenboard mode for the best picture on your projected surface. Eco-mode extends lamp life and reduces fan noise as low as 33 dB. Protect your projector from theft and unauthorized use with the Kensington® security port and PIN lock password.







BRILLIANT PRESENTATIONS MADE EASY

- > Bright in virtually any setting with 2,700 lumens Packs 2,700 lumens in just 6 pounds. It's the bright choice for mobile presenters.
- > BrilliantColor™ technology

 DLP® projectors with BrilliantColor™ feature multi-color processing to produce nearly 50% brighter colors for a vibrant image on the screen that won't fade over time.
- Ultimate video source flexibility Connect a computer or add a video source for dynamic meetings and presentations.
- Supports HD signals including 720p and 1080i Capable of displaying HDTV signals as well as other video and data sources.*
- > Mulitple color correction picture modes
 Blackboard, greenboard, whiteboard and daylight picture
 modes give you the best possible picture regardless of the
 projection surface.
- OnView® controls for superior screen adjustability Screen geometry and color adjustments are precisely made via an easy-to-use on-screen menu.
- > Eco-mode extends lamp life
 Extend the life of your lamp up to
 4,000 hours** and reduce noise output.
- > My Screen Startup
 Customize your startup with a company logo or favorite picture using the MyScreen function.





PJ559D

LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH BrilliantColor™

Pixel Format

Zoom Factor Keystone

Throw Distance

Brightness (max) Contrast Ratio

Aspect Ratio

Throw Ratio

Lens

Size

Lamp

PROJECTOR

DISPLAY









0.0		00.00	000	
and the same	pair fat Aufrit Samuel	. Inches	000	Mary Control

Optiona	I A	ccorioc
Optiona	Acce	ssories

Replacement lampRLC-36
• Soft case with wheels
• Extended Express Exchange® PRJ-EE-05-03
Universal ceiling mount kitWMK-005
 VGA to component video adapter ADPT-002

• Wireless G Presentation Gateway....WPG-150

	Aspect Ratio	4:3 (native), 16:9	
AUDIO	Speakers	2x5-watt	
INPUT SIGNAL	Computer and Video	RGB analog, NTSC, NTSC 4.43, PAL, SECAM, HDTV (480p, 720p, 1080	
	Frequency	F _h :31–79kHz; F _v :56–85Hz	
COMPATIBILITY	PC	Analog: from VGA up to SXGA (scaled)	
	Mac®t	Analog: up to SXGA	
CONNECTOR	RGB (input/output)	15-pin HD, D-sub (x2)	
	Composite Video (input)	RCA jack	
	S-video (input)	Mini-Din 4-pin	
	Component Video (input)	VGA DB-15 to HDTV/component cable*	
	Audio (input/output)	Stereo mini-jack	
	RS-232	6-pin D-sub	
USB		Type B for mouse control only	
POWER	Voltage	100–240VAC, 50–60Hz (universal)	
	Consumption	250W (typ)	
CONTROLS	Basic	Standby/on, input, menu	
	OnView®	Display mode, brightness, contrast, keystone, aspect ratio,	
		blank screen, gamma, white peaking, color temperature,	
		user color, video (sharpness, saturation, tint), display (phase,	
		tracking, H. postion, V. postion), advance (auto source,	
		select, rear, ceiling, eco-mode, lamp hours, lamp reset,	
		auto shutdown, OSD timeout, menu position, factory reset),	
		audio (audio mute)	
OPERATING	Temperature	32-104°F (0-40°C)	
CONDITIONS	Humidity	10–90% (non-condensing)	
	Altitude	0–10,000 ft.	
NOISE LEVELS	Normal / Eco-mode	35 dB (typ) / 33 dB (typ)	
DIMENSIONS	Physical (W x H x D)	8.9" x 4.3" x 8.8" (277mm x 109mm x 223mm)	
WEIGHT	Net	6.0 lb. (2.7 kg)	
	Gross	13.0 lb. (5.9 kg)	
REGULATIONS		UL/cUL, FCC-B, CE, CB, CCC, NOM, C-UL, ICES 003,	
		TUV/GS, GOST-R, HYGIENIC, SASO, UKrSEPRO, RoHS	
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please	
		dispose of in accordance with local, state or federal laws.	
PACKAGE CONTENTS		Projector, power cable, VGA cable, RCA video cable, S-video	
		cable, remote control with built-in laser, soft case, lens cap,	

0.55 DDR DMD, DLP®

Manual zoom, manual focus

200W, 3,500 hrs. normal, up to 4,000 hrs. eco-mode**

27.2"–250" (diagonally)

2,700 ANSI lumens

4:3 (native), 16:9

1024x768 XGA

Vertical ± 40°

47.2"-393.6"

1.97-2.6:1

2,000:1







ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



ViewSonic®

3-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1-year free Express Exchange® service.***

*Optional cables required. **Running eco-mode exclusively can extend lamp life. ***See ViewSonic.com for full details. †Adapter may be required. Analog adapter available from ViewSonic. DLP® and the DLP logo are registered trademarks of Texas Instruments and BrilliantColor[®] is a trademark of Texas Instruments. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13727-00B-10/07] PJ559D-1

WARRANTY