

TX774 Data Projector

Vigorous, Vivid and Versatile – The Ideal Presentation Tool

The Optoma TX774 offers a brightness level of 4000 lumens with a contrast of 2500:1 which produces amazingly bright and crisp images. Perfectly designed for today's demanding environments, the TX774 delivers the perfect picture. The TX774 has a top loading lamp replacement form factor and versatile input options to handle a multitude of video sources for flawless performance.



Features

- Bright at 4000 lumens with a 2500:1 contrast ratio
- Seamless integration with a sleek form factor which allows for easy lamp replacements
- Native XGA (1024 x 768) resolution with support of up to SXGA+ (1400 x 1050)
- Long lasting lamp life of 3000 hours (eco mode)
- Fully featured wireless remote with laser pointer and mouse controls
- Recessed focus and zoom controls eliminate accidental adjustments



Specifications

Brightness

4000 ANSI Lumens

Resolution

Native XGA (1024 x 768)
SXGA+ (1400 x 1050) Maximum

Contrast Ratio

2500:1 (Full On/Full Off)

Lamp Life and Type

2000/3000 Hours (STD/ECO)
280W SHP

Display Type

Single 0.7" DDR DLP® Technology
by Texas Instruments

Throw Ratio

1.8 to 2.1:1 (Distance/Width)

Projection Distance

3.2' to 32.8' (1.0 to 10.0 m)

Image Size

27.5" to 306" (0.7 to 7.8 m)

Aspect Ratio

4:3 Native, 5:4 & 16:9 Compatible

Audio

One Internal 3-Watt Speaker

Displayable Colors

16.7 Million, 256 Shades of Gray

Remote Control

Fully Featured IR Remote with
Laser Pointer and Mouse

Computer Compatibility

VGA, XGA, SVGA, SXGA+ Resized,
VESA, PC and Macintosh Compatible

Video Compatibility

NTSC, PAL, SECAM, EDTV (480p),
HDTV (576i/p, 720p, 1080i)

Monitor Loop Through

D-Sub 15pin VGA Output (Functional
in Both Normal and Standby Modes)

User Controls

Advanced Adjustability Options
Through the On-Screen-Display

I/O Connection Ports

VGA-In, DVI w/HDCP, Composite
Video, S-Video, Two Audio-In, USB,
RS-232, VGA-Out, Audio-Out, +12V
Trigger

Projection Method

Front, Rear, Table Top and Ceiling
Mount

Vertical Refresh Rate

50 to 85 Hz

Keystone Correction

± 15° Vertical

Uniformity

85%

Weight

7.3 lbs (3.3 kg)

Dimensions (W x H x D)

11.81" x 3.46" x 9.61"
(300 x 100.5 x 244 mm)

Noise Level

33dB/31dB (STD/ECO)

Operating Temperature

5 to 35°C, 80% Max Humidity

Storage Temperature

-20 to 60°C, 80% Max Humidity

Power Supply

100-240 Volts, 50-60Hz

Power Consumption

295W, <5W Standby Power

Standard Accessories

AC Power Cord, VGA to VGA Cable,
RS-232 Cable, Composite Video
Cable, Remote Control, Batteries for
Remote, CD-ROM User's Manual,
Lens Cap, Carrying Case, Warranty
Card and Quick Start Guide

Optional Accessories

Bering Ceiling Mount, DVI to HDMI
Adapter and GrayWolfII™ Series
Screens

Warranty

3 Years Optoma Express Replacement
Service, 1 Year on Lamp

UPC

796435 11 656 9