

EPSON PowerLite 715c

The stand alone projector that stands above the rest

Twelve hundred lumens in a 6 lb package-when you size it all up, it's the perfect solution for highly effective mobile presentations. The brightest 6 lb projector in its class, the EPSON PowerLite 715c consistently delivers sharp, vivid images, even in the most challenging lighting conditions. Take it across the hall or around the world. Its award-winning 3-LCD design and exceptional video processing make it the ideal partner for business professionals. Its innovative EPSON EasyMP™ technology facilitates PC-free presentations so you can leave your laptop and cables behind without sacrificing advanced features. Epson's EasyMP technology also delivers lightning-fast image renderings plus 15 transitional effects. And, with its "power-on-and-go" operation, even novice users can be up and running in no time. Having brought over 50 years of engineering excellence to the business world, Epson continues to contribute technologically-advanced, user-friendly solutions like the EPSON PowerLite 715c-the perfect combination of portability and performance.

Ultra bright 1200 lumens

 Projects brilliant images, even in the most challenging lighting conditions

Superior detail and razor-sharp contrast

- 3 LCD technology offers three 0.9" high aperture LCDs for evenly distributed color
- XGA (1024 x 768) resolution delivers sharp, vivid detail
- 400:1 contrast ratio for blacker blacks and whiter whites

Compact and lightweight

 Only 6 lb, allowing travel flexibility for presentations of any size, in any environment

PC-free presenting with EPSON EasyMP

- Auto-run capability just power on the projector and begin presenting
- · Unique editing capability:
 - Rearrange the order of projected images, individually or as a group
 - Select and hide individual images
 - Customize your presentation to your audience
- Easy to use drag and drop your entire presentation using Epson conversion software
- Smooth picture transitions jpeg or bitmap images advance as fast as 40 milliseconds, either automatically or with a mouse click
- 15 PowerPoint*-type transitions includes wipes, dissolves, etc. for smooth, professional presentations
- Make notes and annotations directly on the image and capture them for future reference
- Memory card slot multicard capability including PCMCIA Flash Memory, Compact Flash*, SmartMedia* and Memory Stick* cards

Component video input

 Great for movie viewing; the best video quality of any superportable available

Easy installation, setup and operation

- · Zoom lens adds versatility
- 15° digital keystone correction adjusts the angle, aspect ratio and shape of projected images
- EPSON SizeWise[™] resizing technology supports virtually any computer (Mac or PC) up to UXGA (1600 x 1200)


Renowned Epson service and support

- · Comprehensive 2-year warranty
- · 90-day bulb warranty for added dependability
- EPSON PrivateLine^{5M} dedicated toll-free support line available from 6 a.m. to 6 p.m. PST Monday – Friday. This program is free for the duration of the warranty
- EPSON Road Service Program provides a replacement projector, typically within 24 hours. This program is free for the duration of the warranty
- Interntional warranty in over 45 countries, offered exclusively by Epson

*PCMCIA adapter required, not included



Front View



Back View

EPSON PowerLite 715c Specifications

Projection System	system EPSON original LCD prism technology		Video I/O			
Projection Method LCD Size	Front/rear/ceiling mount/stack 0.9" Dream Panel		Display performance	NTSC: 550 line PAL: 550 line (Depend on observation of multi-burst pattern)		
Driving Method Pixel Number Native Resolution	EPSON Poly-Silicon TFT Active Matrix 786,432 dots (1024 x 768) x 3 XGA		Input signal	NTSC/NTSC4.43/NTSC50/ PAL/M-PAL/N-PAL/PAL60/SECAM		
Aspect Ratio Pixel Arrangement Projection Lens	4:3 (supports 16:9, 5:4) Stripe		Input terminal	Composite video: RCA x 1 S-video: Mini D-sub 15pin x 1 Component video: Mini D-sub 15pin x1		
Type F-number	Manual: zoom/focus 2.0 to 2.2		Audio torrinol	(common with co	imponent video)	
f-number Zoom ratio	35mm to 42mm 1:1.2		Audio terminal Output terminal	RCA x 2 Stereo mini jack		
Lamp Type Life (typical)	150W UHE 1000H			(common analog RGB audio output) (plug in, then speaker off)		
		1.83 to 2.23:1	Control I/O Mouse/Serial I/O			
Screen Width Ratio: (Distance/Width) Screen Size (Projected Distance)		26" to 300"	I/O terminal Mouse compatibility	Din 9pin x 1/USB PS/2, ADB, USB	type B x 1	
Keystone Correction		±15 degrees	Security	Kensington-style	lock provision	
Brightness (typical)		1200 ANSI lumens	Supplied Accessories	Kensington-style	iock provision	
Contrast Ratio 400:1			Power cord, RCA video/audio	Power cord, RCA video/audio cable, remote control,		
Brightness Uniformity (typical) 85%			2 batteries, computer cable HD15/HD15, PS/2 mouse cable, USB mouse cable, soft case, memory card set (8MB Compact Flash Card), application			
Color Reproduction		24 bit; 16.7 mil	software CD-ROM (EMP Slider			
Sound Output 1W monaural			Warranty	Standard two year limited warranty, international warranty, 90-day lamp warranty, EPSON Road Service Program and EPSON PrivateLine dedicated		
Operating Temperature 5° C to 35°C (41°C to 95°F)			warranty, EPSON Road Service			
Power Supply Voltage	100-120V, 200	0-240V ±10%, 50/60Hz AC	toll-free support (U.S. and Car	nada only)		
Power Consumption		220W/4W @ standby mode	Product/Accessory Part Nun EPSON PowerLite 715c project		EMP-715	
Dimensions (including lens	and feet)	10.5"D x 8.4"W x 2.8"H	Samosonite wheeled soft case		ELPKS35	
Weight		6.0 lb	Shoulder case		ELPKS31	
Fan Noise		42db	Shoulder case ATA molded hard shell carrying	g caso	ELPKS32 ELPKS30	
Effective Scanning Frequer Pixel clock Horizontal Vertical	ncy Range	13.5MHz to 162MHz 15KHz to 92KHz 50Hz to 85Hz	Component video interface ca 50" portable screen 60" insta-theatre screen 80" insta-theatre screen		ELPKC19 ELPSC06 ELPSC07 ELPSC08	
Remote Control Features Keystone, picture in picture, special effects, source selection, power, resize, right/left mouse click, EasyMP, volume, presets			Replacement lamp Mac adapter set Kensington security lock Ceiling mount		ELPLP14 ELPAP01 ELPSL01 ELPMB32	
RGB			Suspension adapter for ceiling	mount, 1-1/2" pipe	ELPMBAST	
Display performance Native		nalog RGB I/O 024 x 768	Suspension adapter for ceiling mount, 1" pipe Presentation audio system		ELPMBAPS ELPPAS1	
Resize		600 x 1200	Wireless microphone and spea	akers	ELPCVVS1	
Resize	1	280 x 1024 100 x 600 140 x 480	Support-The Epson Connect Pre-Sales Support U.S. and Ca Automated Technical Support		800-463-7766 800-922-8911	
Input terminal		F.: D. 1. 45.:4	Internet Web Site		www.epson.com	
Video Audio		Aini D-sub 15pin x 1 tereo mini jack	Presenters Online	Presenters On LINE		
Output terminal	3	norco mini jack				
Audio	S	tereo mini jack				



(common video audio output) (plug in, then speaker off)

> Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd. 550 McNicoll, Willowdale, Ontario M2H 2E1

Epson Latin America

6303 Blue Lagoon Drive, Miami, FL 33126

Specifications and terms are subject to change without notice. EPSON is a registered trademark and EasyMP is a trademark of Seiko Epson Corporation. PowerLite is a registered trademark, SizeWise is a trademark and EPSON Connection, PrivateLine and Presenters Online are service marks of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. © Copyright 2000 Epson America, Inc. CPD-10884R1 50K 2/01 GAC