

PJD7383i

INTERACTIVE XGA SHORT THROW PROJECTOR

120HZ AND 3D READY

3D
ready



Interactive presentations come to life.

The PJD7383i is an advanced interactive short throw DLP® projector which includes BrilliantColor™ technology to produce more vibrant colors, while the high brightness and contrast ratios make this projector shine in virtually any lighting situation. The PJD7383i delivers 3000 lumens with a 1024x768 XGA native resolution. Priced at just a fraction of the cost of a traditional 77" interactive white board, the ViewSonic® iProjector provides ultimate flexibility for interactive learning.

1 + 1 = 2



VERSATILE PRESENTATION ANYWHERE

- > **Short throw lens for large, stunning images in small places**
The short throw lens enables large images to be projected from short distances in small rooms with short throw distances. A screen size of 81-inch is possible from just 39 inches.
- > **Interactive pen**
The self contained (IWB) interactive white board functionality along with the included pen works with a variety of software to get the entire class involved in the learning process.
- > **BrilliantColor™ technology**
BrilliantColor technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The 6-segment color wheel enhances the yellow color performance that is key to accurate and vivid color reproduction.

- > **Network control through RJ45**
Schedule, manage and monitor the projector remotely and receive e-mail alerts of projector lamp status. Use the unique integrated clock to perform commands even when the host PC is powered down.
- > **Eco-mode extends lamp life**
Extend the life of your lamp up to 6,000 hours and reduce noise output.
- > **Supports Crestron RoomView® Express**
Manage up to 250 network projectors in real time monitoring and control. Manage assets, schedule events and program email alerts with this amazing software.

CRESTRON
RoomView
express



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

PJD7383i

INTERACTIVE XGA SHORT THROW DLP® iPROJECTOR – 120HZ AND 3D-READY



Optional Accessories

- > Replacement Lamp RLC-057
- > Short throw mount WMK-027
- > Wireless G Presentation Gateway WPG-360
- > USB Wireless Adaptor (802.11b/g/n) WPD-100
- > Extended Express Exchange® PRJ-EE-08-03

Projection Distance		4:3 Aspect Ratio	
M	Feet	M	Inches
0.5	1.6	1.0	39.3
1.0	3.3	2.06	81.1
1.2	3.9	2.44	95.9
1.5	4.9	3.06	120.5
2.5	8.2	5.12	201.6
3.7	12.1	7.56	297.5



ViewSonic Corporation's OMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 . SalesInfo@ViewSonic.com . ViewSonic.com

*Running eco-mode exclusively can extend lamp life. **See ViewSonic.com for full Express Exchange details. Specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Crestron RoomView is a registered trademark of Crestron Electronics, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments and BrilliantColor™ is a trademark of Texas Instruments. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved [15133-03B-10/10] PJD7383i-1

DISPLAY	Type	0.55" Digital Micromirror Device (DLP™)	
	Resolution	XGA 1024x768 (Native)	
	Lens	Fixed Lens / Manual Focus	
	Keystone	Vertical digital keystone correction: +/- 40 degrees	
	Display Size (Diagonal)	30"-300" / 0.762m-7.62m	
	Throw Distance	0.37m-3.7m / 1.2ft-12.21ft	
	Throw Ratio	0.61:1	
	Lamp	210 watt	
	Lamp Life (Normal / Eco-mode)	4000 / 6000 hours*	
	Brightness	3000 Lumens	
	Contrast Ratio	2000:1 static (typ); 3000:1 (dynamic)	
	Aspect Ratio	4:3 (native) and 16:9, Auto	
	Color Depth	24 bits, 16.7M color (8+8+8)	
Color Wheel	6-Segment RGBCYW / 7200rpm		
Color Gamut	90% NTSC 1931 CIE		
INPUT SIGNAL	Computer and Video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SECAM (B, D, G, K, K1, L), SD 480i/576i, ED 480p/576p, HD 720p/1080i	
	Frequency	F _H : 31-100KHz, F _V : 48-120Hz	
COMPATIBILITY	PC	VGA to UXGA	
	Mac®	Up to UXGA (scaled)	
CONNECTOR	RGB Input	15-pin mini D-sub (x2)	
	RGB Output	15-pin mini D-sub	
	Composite Input	RCA jack	
	S-video Input	4-pin mini-DIN	
	Audio Input	3.5mm mini jack (x1), RCA (L/R)x1	
	Audio Output	3.5mm mini jack	
	Mic-In	3.5mm mini jack	
	12V trigger	2mm/1A	
	Control	RS-232 (DB-9)	
	LAN	RJ-45	
	USB	Type A for PC-less slide show presentation – supports JPEG, BMP, TIFF, PNG, GIF from USB flash drive, optional wireless USB adapter. Mini-B for direct presentation from PC (not MAC compatible) PointBlank, mouse control	
	AUDIO POWER	Speaker	10W (x1)
		Voltage	100-240VAC (Auto Switching), 50/60Hz (universal)
CONTROLS	Consumption	296W (typ) / <1W (stand-by mode)	
	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, auto, mode/enter, source	
OPERATING CONDITIONS	OSD	Display: Screen color, Aspect ratio, Keystone, Position, Phase, H. Size, Zoom, 3D sync, 3D sync invert, Color Management Picture: Color Mode, Reference Mode, Brightness, Contrast, Color, Tint, Sharpness, Brilliant Color, Color Temp., Save Settings Source: Quick Auto Search, PointBlank System Setup (Basic): Language, Projector Position, Auto Power Off, Blank Timer, Panel Key lock, Splash Screen, Screen Capture, Message, LAN Control Settings, Standby Settings System Setup (Advanced): High Altitude Mode, DCR, Audio Settings, Menu Settings, Closed Caption, Lamp Settings, Presentation Timer, Security Setting, Reset All Settings Information: Current System Status	
	Temperature	32°F-104°F (0°C-40°C)	
	Humidity	10%-90% (non-condensing)	
	Altitude	0-6,000 ft. (1,800m), operational up to 10,000 ft. (3048m)	
	NOISE LEVEL	Normal / Eco-mode	32dB / 27dB
		Physical	11.4" x 5.0" x 10.0" / 290mm x 126mm x 254mm
	DIMENSIONS (W x H x D)	Packaging	15.5" x 16.3" x 9" / 395mm x 415mm x 228mm
		WEIGHT	Net
	Gross		13.2 lb. (6 kg)
	REGULATIONS	CB, UL, cUL, FCC (including ICES-003), CE, UL-Argentina, NOM, TUV-GS, GOST-R, SASO, Ukraine, PSB, C-Tick, Korean-eK, CCC, Hygiene, WEEE, RoHS	
		PACKAGE CONTENTS	
	WARRANTY	ViewSonic projector, power cable, VGA cable, mini type B to type A USB cable, interactive pen, laser remote control with batteries, lens cap, soft case, Quick Start Guide, ViewSonic Wizard CD (with User Guide)	
		3-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year Express Exchange® service**	

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com