



EPSON PowerLite® 73c

The big value in brilliant multimedia projectors

Looking for an incredible value in XGA multimedia projectors? Meet the EPSON PowerLite 73c, a sleek 6.4 lb projector that delivers 1500 lumens of brightness and the highest standards of image quality. Designed with innovative EPSON 3-LCD technology for vivid images and superior color saturation, this powerful performer shines bright in any situation.

With unique features including Epson's exclusive auto keystone correction, the PowerLite 73c is ideal for all your presentation needs. It even offers monitor out capability, so you can use the monitor as a prompt. Plus, with a convenient remote control, operation couldn't be easier!

Perfect for businesses, schools, or universities, the economical EPSON PowerLite 73c is backed by renowned Epson service and support. In fact, every EPSON PowerLite projector has met stringent quality control standards from the design table to the shipping dock, to ensure the highest degree of performance. And, experienced professionals who service and sell multimedia projectors choose Epson 5:1 as the most reliable.

Brilliant 1500 lumens; weighs just 6.4 lb

• Incredible brightness from a sleek, travel-friendly projector

Highest standard of image quality, even in well-lit rooms

- Three 0.7" high-aperture EPSON LCDs for rich color saturation across the screen
- 500:1 contrast ratio for blacker blacks and whiter whites
- XGA (1024 x 768) resolution for sharp, vivid detail



Where Projectors Roam Free

Easy setup and operation

- Monitor out capability so you can display images on a monitor and screen simultaneously (active even in standby mode)
- Exclusive auto keystone correction 15° digital keystone correction that automatically engages without manual adjustments
- Optical zoom lens for flexible placement and positioning
- Easy-to-use remote control that's the size of a credit card and is stored within the projector
- Remote USB mouse compatibility (Type A and Type B)
- EPSON SizeWise[™] resizing technology supports virtually any computer (Mac or PC) up to SXGA (1280 x 1024)
- Cable lock feature for security conscious environments
- Start Here Kit gets first-time users projecting in just minutes

State-of-the-art video performance

- Composite, component (optional cable required), and S-video input capabilities
- HDTV-ready, supports 480i, 480p, 720p, and 1080i formats (optional cable required)

Renowned EPSON service and support (all free for the duration of the warranty)

- Comprehensive two-year warranty
- · 90-day bulb warranty for added dependability
- EPSON Road Service Program provides a replacement projector, typically within 24 hours
- EPSON PrivateLinesM dedicated toll-free support line available from 6 a.m. to 6 p.m. PST Monday Friday. Calls are answered live, typically in under a minute.
- Two-year international warranty in over 45 countries



USB type A

computer/component
S-video
out
composite video

Front View

Back View USB type B

computer audio

EPSON PowerLite 73c Specifications

Projection System	EPSON original LCD prism technology	
Projection Method	Front/rear/ceiling mount	
LCD	0.71	
Size Driving method	0.7" EPSON Poly-Silicon TFT Active Matrix	
Pixel number	786,432 dots x 3 (1024 x 768) LCDs	
Native resolution	XGA	
Aspect ratio	4:3 (supports 16:9, 5:4)	
Pixel arrangement	Stripe	
Projection Lens		
Type - number	Manual: zoom / focus	
-number -number	1.70 – 1.87 21.3 – 25.6mm	
Zoom ratio	1.0:1.2	
.amp		
Гуре	165W UHE	
ife (typical)	1500H	
Screen Width Ratio (distance)	width) 1.48 to 1.71:1	
icreen Size (projected distance)	30" to 300" (0.9m to 10.5m)	
Keystone Correction	Vertical: +/-15°, Auto Keystone Correction	
Brightness (typical)	1500 ANSI lumens	
Contrast Ratio	500:1	
Brightness Uniformity (typic	al) 85%	
Color Reproduction	24 bit; 16.7ml	
Audio Output	1W Monaural	
·		
Operating Temperature	41°F to 95°F (5°C to 35°C)	
Power Supply Voltage	100-120V / 200-240V +/-10%, 50/60Hz AC	
ower Consumption	240W/2.6W at sleep mode	
Dimensions (excludes lens and f	9.45" x 12.41" x 3.43"	
Dimensions (includes lens and fe	9.45" x 12.41" x 3.82"	
Weight	6.4lb/2.9kg	
an Noise	36db	
Effective Scanning Freque	ncy Range	
Pixel clock	13.5MHz to 162MHz	
Horizontal Vortical	15KHz to 92KHz	
/ertical	50Hz to 85Hz	
Remote Control Features	Keystone, source selection, power, color mode, page up/page down, volume, presets, e-zoom, a/v mute, freeze	
Operating Angle	Right/Left +/- 30 degrees Upper/Lower +/- 15 degrees	
Operating Distance	20ft (6m)	
RGB	· · · · ·	
pisplay performance	Analog RGB I/O	
Native Resize	1024 x 768 1280 x 1024, 640 x 480	
nput terminal		
Video	Mini D-sub 15 pin	
	Storee mini jack	
Audio	Stereo mini jack	
	Stereo mini jack Mini D-sub 15pin (monitor out)	

Video I/O			
Display performance		NTSC: 550 lines, PAL: 550 lines (Depends on observation of the multi burst pattern)	
Input signal	NTSC, NTSC4.43, PAL, M-PAL, N-PAL, PAL60, SECAM HDTV: 480i, 480p, 720p, 1080i		
Input terminal Video Audio	Composite Video: RCA (Yellow) x 1; S-video: Mini DIN; Component Video: Mini D sub 15pin (in common with Analog RGB connector); Video-RGB: Mini D-sub 15pin (in common wit Analog RGB connector) RCA (White/Red) x 2		
Audio signal	500m Vrms/47Kohm		
Control I/O			
I/O terminal	RS-232C		
Security	Kensington®-style lock pro	ovision	
	emote control with lithium batt eo cable, USB A/USB B Mouse		
Product/Accessory Part EPSON PowerLite 73c Pro Replacement lamp Replacement remote Samsonite wheeled soft of Samsonite Notebook/proj ATA molded hardshell cast Ceiling mount Suspension adapter False ceiling plate Distribution amplifier Component video cable S-Video Cable Mac adapter set 50" portable screen 60" portable spop-up scre 80" portable pop-up scre 80" portable pop-up scre High resolution documen Motion presentation cam High resolution documen Kensington security lock	Numbers jector asse jector soft shoulder bag se een jeen t imager jera	V11H106020 V13H010L2 V12H007T06 ELPKS24 ELPKS45 ELPMB36 ELPMBFC1 ELPDA01 ELPKC15 ELPSC06 ELPSC06 ELPSC06 ELPDC02 ELPDC02 V12H064020	
Support-The EPSON Co Pre-Sales Support U.S. an		800-463-776	
Automated Technical Support		800-922-891	

Sales: 1300 88 11 79



www.Projectisle.com.au

www.epson.com presentersonline.com

Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada, Ltd.

Internet Web Site

Presenters ONLINE™

3771 Victoria Park Avenue, Toronto, Ontario M1W 3Z5

Epson Latin America

6303 Blue Lagoon Drive, Suite 195, Miami, FL 33126

Specifications and terms are subject to change without notice. EPSON is a registered trademark of Seiko Epson Corporation. PowerLite is a registered trademark, SizeWise is a trademark and EPSON Connection, PrivateLine and Presenters Online are service marks of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. © Copyright 2002 Epson America, Inc. CPD-15074 15K 11/02 CB

Printed on Recycled Paper