

XEED WUX500

Compact, high-performance WUXGA professional installation projector with versatile connections

Enjoy superior image quality and versatile connections with this WUXGA compact installation projector, which features LCOS technology, constant 5000 lumens brightness and a Canon quality 1.8x zoom lens plus HDBaseT and Wi Fi.



- Achieve detailed, ultra-realistic images with native WUXGA resolution (1920 x 1200 pixels) and Full HD capability
- Enjoy a vivid 5000 lumens constant* brightness and native 2000:1 contrast ratio
- Create smooth, seamless images with vivid, accurate colours using LCOS panel and AISYS technology
- 1.8x zoom lens with powered lens shift, zoom and focus for fast and accurate installation
- Connect to a wide variety of devices thanks to HDBaseT connection and Wi Fi for wireless LAN with Network Multi Projection (NMP.J)
- Advanced imaging features include hardware edge blending, picture-by-picture and four corner keystone correction
- PC-free multi projection via USB using up to nine projectors
- HDMI and RJ-45 network ports
- Easy access to the lamp and air filter helps keep maintenance costs down
- Energy efficient with up to 5000h lamp life and only 30dBa in ECO mode



An enhanced warranty service as standard

The Canon Three Year Enhanced Warranty Service helps keep your installation operational.

Three Year*

XEED projectors are covered by a 3 year swap out warranty*. Total peace of mind. If our technical support team cannot get your projector up and running through our 1300** support line, then they will organise the unit to be replaced.

*Canon projectors come with 36 month warranty on the main projector unit + 6 month warranty on the lamp return to base as standard.

**Available on products covered by Australian warranty. Swap out units may be new or factory refurbished models. Delivery may take up to 5 business days, and will vary depending on Customer's location. Customers are responsible for securely packaging the faulty projector for courier pick up. Ownership of the faulty projector will pass to Canon upon delivery.

**Projector Support Line - 1300 799 604 or email

Based on a single image size. Brightness may decrease by up to 5%.

ProSelecta

View :: Compare :: Select - www.ProSelecta.com

KEED WUX500

Compact, high-performance WUXGA Professional installation projector with versatile connections

Enjoy superior image quality and versatile connections with this WUXGA compact installation projector, which features LCOS technology, constant 5000 lumens brightness and a Canon quality 1.8x zoom lens plus HDBaseT and Wi-Fi, zoom lens plus HDBaseT and Wi-Fi.

Technical Specifications

PANEL

Type	LCOS reflective display, TFT Active Matrix
Size and Number	0.71" diagonal, 3 panels
Aspect Ratio	16:10
Native Resolution	1920 x 1200 (WUXGA), 2304000 pixels

OPTICS

Lamp Type	250W NSHA
Lens F Number and Focal Length	F2.8; f=21.7 – 39.0 mm
Zoom Magnification and Control	1.8x Manual
Focus Control	Manual
Lens Shift	Vertical: 0% to +60%, Manual Horizontal: +/-10%, Manual

IMAGE AND AUDIO

Brightness	5000 lumens (3800 lumens in Eco Mode)
Brightness Uniformity	90%
Contrast Ratio	2000:1 (full on / full off)
Projection Distance Coverage	1.2m – 16.2m (3.0m – 5.4m for 100" image)
Screen Size	40" - 300" (86 x 54cm - 646 x 404cm)
Throw Ratio	1.39 - 2.51 : 1
Keystone Correction Range	Vertical: +/-20° Horizontal: +/-20°
Digital RGB Compatibility	WUXGA / UXGA / WSXGA+ / SXGA+ / WXGA+ / FWXGA / WXGA / SXGA / XGA / SVGA / VGA
Analogue RGB Compatibility	WUXGA / UXGA / WSXGA+ / SXGA+ / WXGA+ / FWXGA / WXGA / SXGA / XGA / SVGA / VGA
Digital Video Scan Systems	1080p / 1080i / 720p / 576p / 480p
Component Video Scan Systems	1080p / 1080i / 720p / 576p / 576i / 480p / 480i
Supported File Types	JPEG still image

Built-in Speaker

5.0W RMS, Monaural

PORTS AND CONNECTORS

Digital RGB Input	DVI-I 29-pin (shared)
Digital Video and Audio Input	HDMI (with Deep Colour)
Analogue RGB Input 1	DVI-I 29-pin (shared)
Analogue RGB Input 2	Mini D-Sub 15-pin (Component via optional adaptor cable)
Audio Input 1	3.5 mm stereo mini-jack
Audio Input 2	3.5 mm stereo mini-jack
Audio Output	3.5 mm stereo mini-jack (variable level)
USB Port	USB Type A
Service Port / Projector Control	Mini D-Sub 9-pin
Network Port	RJ-45 (HDBaseT) RJ-45 (1000BASE-T / 100BASE-TX / 10BASE-T)
Wired Remote Control	3.5 mm stereo mini-jack

MECHANISMS

Front Elevation Mechanism	Two rotary feet, 6° maximum image elevation
---------------------------	---------------------------------------------

RATINGS

Dimensions (W x H x D)	337 mm x 136 mm x 370 mm
Weight	5.9 kg
Power Source	100V - 240V AC, 50/60Hz
Power Consumption	Normal Mode: 365W / Eco Mode: 295W / Standby: 1.3W / Standby (LAN & HDBaseT off): 0.2W
Noise Level	Normal Mode: 37dBA / Eco Mode 30dBA
Operating Environment	0°C to +40°C
Storage Environment	-10°C to +60°C
Warranty	3 Years Main Body; 6 month on lamp

All data is based on Canon standard testing methods except where indicated. Subject to change without notice.