

# CP-RX70



## LCD PROJECTOR


Built for portability and performance the CP-RX70 weighs just 1.7Kg. Combining a short throw lens, low noise level and Quick Start function, this compact projector can be used in a variety of ways fitting perfectly into any environment.

- 2000 Lumens
- Light weight 1.7kg
- Short throw lens – 60" @ 1.8 m
- Low noise level 29dB
- Auto Vertical Keystone Correction
- Quick start (4 seconds)
- Instant OFF




**HITACHI**  
Inspire the Next

# CP-RX70



Unit: mm



## Image Size 4:3

Screen Size (Diagonal)	Projection Distance (a)		Screen Height (cm)	
	min. (m)	max. (m)	b (top)	c (bottom)
40" (1.0)	1.2	1.4	52	9
60" (1.5)	1.8	2.2	78	13
100" (2.5)	3.0	3.6	131	22
150" (3.8)	4.5	5.4	196	33
200" (5.1)	6.1	7.3	261	44
300" (7.6)	9.1	10.9	392	65

## CP-RX70 Technical Specifications

### OPTICAL

LCD Panel		0.63" P-Si TFT x 3 with Microlens
Resolution		XGA: 1024 dots x 768 lines
Brightness	Normal Mode	2000 ANSI Lumens
	Bright Mode	1500 ANSI Lumens
Contrast Ratio		500:1
Lens		F1.7 ~ 1.9 (f=19.2 ~ 23.0mm) Manual x 1.2 zoom
Lamp		UHB160W
Projection Distance		0.9 ~ 9.1 m (WIDE), 1.1 ~ 10.9 m (TELE)
Distance to Width Ratio (:1)		1.5 (WIDE), 1.8 (TELE)
Diagonal Display Size		30~300" (60"@1.8m, Wide)
Number of Colour		8 Bit/colour, 16.7M colours
Keystone		6:1 upward shift, fixed

### COMPATIBILITY

Computer Compatibility		IBM Compatible VGA, SVGA, XGA, SXGA/SXGA+, UXGA Capability, MAC 16"
Video Compatibility		NTSC/PAL/SECAM/PAL-M,N/NTSC4.43 SDTV: 525i(480i), 525p(480p), 625i(576i) HDTV: 750p (720p@60Hz), 1125i(1080i@50/60Hz)
Plug & Play		DDC2B
Frequency Range		FV 56~120Hz, FH 31.5~106kHz

### FEATURES

Speakers		1.0 W x 1
Other:		Mirror Reverse Image, Up-side Down Image, Freeze, Magnify, Blank, Equalizing Gamma Correction, Colour temperature Adjustment, Picture mode (Normal, Cinema, Dynamic, Whiteboard and Blackboard mode, 2-3 Pull Down, Progressive Scan, Video noise reduction, Overscan (Video, S-Video, Component signal), Resolution setting, Frame Lock, Audio ports assign, Source naming, Quick start (4 Seconds), Instant off, Auto signal search, MyScreen PIN Lock, Keypad lock, Kensington lock, PIN Security Lock, MyScreen, My Memory, My Button, Easy lamp replace from top, Easy filter change with sliding system
OSD Languages		17 Languages

### CONNECTIONS

Computer Input		15-pin Mini D-sub x 2
Video Input		Composite x 1, S-Video Jack x 1 Component x 1 (shared with D-sub1)
Audio Input		Stereo Mini Jack x 1
Audio Output		Stereo Mini Jack x 1

### POWER

Power Supply		90~132/198~264V, Auto Switching
Power Consumption		250W

### PHYSICAL

Dimensions (W x H x D)		274 x 59 x 205mm (excluding feet and extrusions)
Weight		1.7kg
Noise Level		29dB (Whisper Mode)/35dB (Normal Mode)
Air Filter		MU03602

### MISCELLANEOUS

Lamp indicator light, Power light, Ceiling Mount image, Rear Projection Image

### CERTIFICATION

UL/c-UL, FCC Part 15, Class B, AS/NZS CISPR22 Class B, CE

### ACCESSORIES SUPPLIED

Remote Control with batteries, RGB Cable, Power Cord, Softcase, Lens Cap (& strap), Quick Guide

### OPTIONAL ACCESSORIES

Replacement Lamp DT00781

## Image Size 16:9

Screen Size (Diagonal)	Projection Distance (a)		Screen Height (cm)	
	min. (m)	max. (m)	b (top)	c (bottom)
40" (1.0)	1.3	1.6	49	1
60" (1.5)	2.0	2.4	73	2
100" (2.5)	3.3	4.0	122	3
150" (3.8)	4.9	5.9	182	4
200" (5.1)	6.6	7.9	243	6
300" (7.6)	9.9	11.9	365	9