



P1266 PROJECTOR

DLP Technology – Entertainment all rounder

The P1266 provides the home entertainment and SMB/classroom presentation performance expected of much more expensive projectors. With optimized color performance via 2500 ANSI Lumens brightness and XGA resolution, the display is clear and vibrant. Other notable features include an HDMI™ port, a 6-segment color wheel with 3X rotation speed, support for both 4:3 displays and widescreens through Acer SmartFormat, and Acer ColorBoost II and EcoProjection technologies. All told, the P1266 offers a smart blend of high performance and great value.

Why P1266 Projector?

- Resolution XGA (1024 X 768), Maximum UXGA (1600 x 1200), WSXGA+ (1680 x 1050)
- Contrast Ratio 2000:1
- Brightness 2,500 ANSI Lumens (Standard), 2,000 ANSI Lumens (ECO)
- Projection Distance 3.3' (1.0m) ~ 32.0' (9.8m)



SmartFormat



Technical Specifications

Model Name	P1266
Resolution	Native XGA (1,024 x 768) Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p, (480i, 576i)
Aspect Ratio	4:3 (Native), 16:9
Contrast Ratio	2000:1
Displayable Colours	134 Million Colors
Brightness	2,500 ANSI Lumens (Standard), 2,000 ANSI Lumens (ECO)
Projection Lens	F = 2.41 ~ 2.66, f = 18.17mm ~ 21.81mm 1:1.2 Manual Zoom and Manual Focus
Projection Screen Size	26" (65cm) ~ 300" (762cm)
Projection Distance	3.3' (1.0m) ~ 32.0' (9.8m)
Throw Ratio	62"@2m (1.60 ~ 1.92:1)
Horizontal Scan Rate	31.5 ~ 100 kHz
Vertical Scan Rate	50 ~ 85 Hz
Lamp Type / Life	Osram 180 W user replaceable P-VIP lamp 3,000 Hours (Standard), 4,000 Hours (ECO)
Keystone Correction	+/-40 Degrees (Vertical)
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Audio	One Internal Speaker with 2 watts Output
IR Remote Control	IR remote control with laser pointer & PgUp/PgDn functions
Digital Zoom	2x
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	235 Watts (Operation), <5 Watts (Standby)
Operating Temperature	5°C ~ 35°C / 41°F ~ 95°F
Noise Level	31 dBA (Standard mode), 28 dBA (ECO mode)
Input Interface	Analog RGB/Component Video (D-sub) x 1, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, HDMI (Video, HDCP) x 1, PC Audio (Stereo mini jack) x 1
Output Interface	Analog RGB (D-sub) x 1
Control Interface	USB (Type B) x 1 RS232 (Mini DIN) x 1
Weight and Dimensions	5.5 lbs (2.5 Kg) kg 269 x 206 x 96 mm (8.8" x 6.7" x 3.1")
Compliance	C-Tick (AS/NZS 60950)
Standard Warranty	2 year return to base

Product specifications are subject to change without prior notice. Acer & the Acer logo are registered trademarks of Acer Inc., and Acer America Corp. All other products, brand names, or company names are trademarks & registered trademarks of their respective companies. Acer shall not be liable for technical, editorial or pictorial errors, inaccuracies or omissions contained herein; nor for any consequential damage resulting from the furnishing, performance, or use of this material. * Maximum hours. Actual hours depend on usage and configuration. ** Contact Acer for warranty details.

¹ Specifications vary depending on model.