
EB-L20000U



DATASHEET / BROCHURE



Compact 20,000-lumen WUXGA laser installation projector that offers fit-and-forget reliability and great performance.

The EB-L20000U is designed to be used at events, festivals, visitor attractions, large auditoriums, trade shows and shopping centres, as well as for corporate and educational purposes.

A futureproof 20,000 lumen projection solution

Easily slots into an existing infrastructure. It uses the same lenses as Epson's popular EB-L1000 series projectors that are native-4k compatible.

Easy installation

Light, compact and easy for a single person to transport and install. The EB-L20000U offers 360-degree installation and can project from any angle, as well as in portrait mode. It also features built-in camera for automatic edge-blending.

Trusted reliability

A five-year, 20,000-hour warranty, coupled with inbuilt self recalibration means these projectors can be installed and forgotten about. The built-in camera enables remote adjustment and troubleshooting.

KEY FEATURES

- Impressive brightness 20,000 lumens
- Resolution
 Native WUXGA resolution
- Compatibility Epson Projector Professional Tool software
- Built-in high resolution camera For diagnostics, set-up, adjustment and automatic edge-blending
- Durable reliability Sealed optical unit to protect against dust and smoke





PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology
LCD Panel	1.03 inch with C2 Fine
IMAGE	
Colour Light Output	20,000 lumen- 14,000 lumen (economy) in accordance with IDMS15.4
Resolution	WUXGA, 1920 x 1200, 16:10
Contrast Ratio	2,500,000 : 1
Native Contrast	2,000 : 1
Laser Light source	20,000 Hours Durability High, 30,000 Hours Durability Eco
White Light Output	20,000 lumen - 14,000 lumen (economy) in accordance with ISO 21118:2012
Portrait Colour Light Output	20,000 lm
Portrait White Light Output	20,000 lm
Keystone Correction	Manual vertical: \pm 45 °, Manual horizontal \pm 30 °
Colour Reproduction	upto 1.07 billion colours
OPTICAL	
Projection Ratio	1.57 - 2.56:1
Lens Shift	Motorized - Vertical ± 60 %, horizontal ± 18 %
Image Size	60 inches - 1,000 inches
Focus	Motorized
Zoom	Motorized, Factor: 1 - 1.6
Lens position memory	10 positions
Projection Distance Wide	2 m - 24.4 m
Projection Distance Tele	3.3 m - 55.6 m
Projection Distance Wide/Tel	e 1.99 m - 55.63 m
Projection Lens F Number	1.8 - 2.3
Focal Distance	36 mm - 57.3 mm
CONNECTIVITY	
Interfaces	HDBaseT, BNC in, DVI in, VGA out, VGA in, Ethernet interface (100 Base-TX / 10 Base-T), RS-
	232C, USB 2.0 Type B (Service Only), Wireless LAN b/g/n (2.4GHz) (optional), HDMI (HDCP
	2.2), 3G-SDI Input, DC Power Output (900mA), 3G-SDI Output, Ethercon LAN
ADVANCED FEATURES	
	Cinama Dunamia Dresontation DICOM SIM Multi Drejection DT700
Video Colour Modes	Cinema, Dynamic, Presentation, DICOM SIM, Multi Projection, BT709
Projector control	via: AMX, Crestron (Network), Extron
GENERAL	
Energy Use	1,860 W, 1,123 W (economy), 0.5 W (standby), On mode power consumption as defined in
	JBMS-84 1,743 W
Heat Dissipation	6,324 BTU/hour (max)
Product dimensions	620 x 790 x 358 mm (Width x Depth x Height)
Product weight	49.6 kg
Noise Level	Normal: 45 dB (A) - Economy: 38 dB (A)
OTHER	
Warranty	60 months Carry in or 20,000 h

EB-L20000U

WHAT'S IN THE BOX

- Remote control incl. batteries
- Quick Start Guide
- Power and signal cable (3 m)
- Cable cover
- CD Manual



OPTIONAL ACCESSORIES

- Stacking Frame ELPMB57 L12000Q/L20000U (EVO) V12H989B57
- HDBaseT Transmitter ELPHD01 V12H547041

OPTIONAL LENSES

- Lens ELPLW08 Wide throw V12H004W08
- Lens ELPLL08 Long throw G7000/L1000 series V12H004L08
- Lens ELPLM10 Mid throw 3 G7000/L1000 series V12H004M0A
- Lens ELPLM11 Mid throw 4 G7000/L1000 series V12H004M0B
- Lens ELPLM15 Mid Throw L1500/L1700 Series V12H004M0F
- Lens ELPLU03 G7000 & L1000 Series ST off axis 1 V12H004U03
- Lens ELPLU04 G7000 & L1000 Series ST off axis 2 V12H004U04
- Lens ELPLW06 L1500U/1505U wide zoom 2 V12H004W06
- Lens ELPLX02 UST Lens L1500/1700 Series V12H004X02

LOGISTICS INFORMATION

SKU	V11H833840
EAN code	8715946663227
Country of Origin	China

EB-L20000U



