

EB-PU1008B WUXGA 3LCD Laser Projector with 4K Enhancement¹



Product shown with lens.
Lens sold separately.

Projectors

Large Venue

Premium, compact large-venue laser projector with 4K Enhancement¹.

Best-in-Class Color Brightness² — 8,500 lumens color/white brightness³ from a compact large-venue laser projector

Exceptional widescreen display — native WUXGA with 4K Enhancement Technology¹ (1920 x 1200 x 2); accepts 4K content and provides up to 4.6 million pixels onscreen

Worry-free operation — features a virtually maintenance-free 20,000-hour laser light source and air filter⁴

Simplified installation features — 11 optional powered lenses including ultra short-throw with .35 throw; inputs including HDBaseT™ and HDMI® (HDCP 2.3)

NFC function built-in⁴ — reduce installation time of multiple projectors; read and write setting information using Epson's mobile app

Clip-on optional external camera — access powerful automated tools including auto color calibration⁵, screen matching of multiple projectors⁶, tiling assist⁷ for edge blends, and the stacking assist⁸ function

Lifelike images — high native contrast ratio, HDR support and scene adaptive gamma correction for more realistic images and easy-to-read presentations

Optional external air filter — extend the filter maintenance cycle in dusty environments

Dynamic projection capabilities — advanced built-in edge blending, image warping and shape overlay features for a variety of applications; direct content playback from USB storage media

Customized performance — brightness modes to maximize light source life and provide a consistent brightness level

Powerful remote management — control and monitor projector status via the Epson Projector Management app for Windows®



Specifications

Projection System High-aperture Epson® 3LCD, 3-chip technology
Projection Method Front/rear/ceiling mount
Driving Method Poly-silicon TFT Active Matrix
Pixel Number 2,304,000 dots (1920 x 1200) x 3 chips
Signal Input Maximum Display Resolution: 4096 x 2160 (resizing display) Display Resolution: 1920 x 1200 pixels
Native Resolution WUXGA with 4K Enhancement¹ (1920 x 1200 x2)
Resolution on Screen WUXGA with 4K¹ Enhancement/4.6 million pixels¹
Aspect Ratio Supports 4:3, 16:9, 16:10
Pixel Arrangement Cross stripe
Color Brightness³ Color Light Output: 8,500 lumens
White Brightness³ White Light Output: 8,500 lumens
Contrast Ratio 2,500,000:1 (Dynamic Contrast: On)
Brightness Uniformity (typical) 85%
Color Reproduction Up to 1.07 billion colors
Keystone Correction
 Vertical: ±45 degrees;
 Horizontal: ±30 degrees
Illumination Technology Laser Phosphor

Projection Lens (Standard)

See website for information on optional lenses.
Standard Lens ELPLM08 (sold separately)
Type Powered shift/focus/zoom
F-number 1.7 – 2.3
Focal Length 24.0 mm – 38.2 mm
Zoom Ratio Optical zoom 1 – 1.6x
Throw Ratio Range 1.45 – 2.32
Lens Shift Vertical: ±67%; horizontal: ±30%

Other Features

Operating Temperature 32 ° to 113 °F (0 ° to 45 °C)
Power Supply Voltage 100 – 240 V ±10%, 50/60 Hz AC
Power Consumption
 448W (Normal, Custom)
 379W (Medium, Quiet, Extended)
 2.0 W Standby (Communication on)
 0.5 W Standby (Communication off)
Fan Noise 33dB (Normal Mode), 31dB (Medium Mode), 29dB (Eco Mode)
Security Security cable hole, lens lock, Kensington lock provision, wireless LAN unit lock

Video I/O

Input Signal Input Video Signal (HDMI, DVI-D and HDBaseT ports) 480i/480p/576i/576p/720p/1080i/1080p/3840 x 2160/4096 x 2160

Interfaces

DVI-D x 1
 HDMI (HDCP 2.3) x 1
 HDBaseT x 1
 RGB D-sub 15pin
 Variable audio out: Mini Stereo x 1
 USB connector Type-B x 1
 USB connector Type-A x 2
 Serial: RS-232c x 1
 Remote Stereo Mini
 Network: RJ-45



Dimensions (W x D x H)

Excluding Feet, Lens 21.5" x 6.5" x 17.2"
Weight 35.9 lb

Remote Control

Features Power, source search selection, lens shift, zoom, focus, test pattern selection, A/V mute, freeze, user ID, auto, aspect, color mode, number, page up and down, E-zoom, volume, help, menu, enter, esc and pointer functions
Operating Angle
 Angle Front: Right/Left: 60 to +60 Upper/Lower +30 to 20 degrees
 Angle Rear: Right/Left 30 to +30 Upper/Lower +50 to +10 degrees
Operating Distance 98 ft

Eco Features

RoHS compliant Recyclable product⁹
 Epson America, Inc. is a SmartWay® Transport Partner¹⁰

Support

Epson ConnectionSM
 Pre-sales support U.S. and Canada 800-463-7766
 Internet website www.epson.com

Service Programs

The projector has a limited warranty of 3 years. Epson Road Service program with free Next-Business-Day replacement¹¹, PrivateLine® dedicated toll-free support (U.S. and Canada only)

What's in the Box

EB-PU1008B projector, power cable, remote control with 2 batteries, cable cover, lens connector cap, user guide and warranty sheet

Ordering Information

ELPLAF46	V13H134A46
External Air Filter (ELPAF63)	V13H134AD0
Ultra Short-throw lens (ELPLX01S)	V12H004X0A
Ultra Short-throw lens- White (ELPLX01WS)	V12H004Y0A
Short-throw #1 zoom lens (ELPLU03S)	V12H004UA3
Short-throw #2 zoom lens (ELPLU04)	V12H004U04
Wide-throw #1 zoom lens (ELPLW05)	V12H004W05
Wide-throw #2 zoom lens (ELPLW06)	V12H004W06
Wide-throw #3 zoom lens (ELPLW08)	V12H004W08
Middle-throw #1 zoom lens (ELPLM08)	V12H004M08
Middle-throw #2 zoom lens (ELPLM15)	V12H004M0F
Middle-throw #3 zoom lens (ELPLM10)	V12H004M0A
Middle-throw #4 zoom lens (ELPLM11)	V12H004M0B
Long throw zoom lens (ELPLL08)	V12H004L08
External Camera (ELPEC01)	V12HA46010
Rigging frame	ELPMB59
HDBaseT transmitter (ELPHD01)	V12H547020
Wireless LAN module (ALPAP11)	V12H005A02
Projector Ceiling Mount (ELPMB67)	V12HA54010
Suspension Adapter (ELPPF15)	V12HA55010

¹ 4K Enhancement Technology shifts each pixel to surpass Full HD resolution on screen. | ² Color brightness measured per IDMS 15.4. Additional colors and picture modes tested. Top-selling Epson 3LCD projectors vs. comparable top-selling 1-chip DLP projectors based on NPD sales data for October 2019 – September 2020. COLOR BRIGHTNESS WILL VARY BASED ON USAGE CONDITIONS. | ³ Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | ⁴ NFC enabled device required | ⁵ Requires Epson external camera | ⁶ Requires an Epson external camera for each projector. | ⁷ Requires Epson external camera for each projector and the Epson Projector Professional Tool App | ⁸ Requires Epson external camera for each projector | ⁹ For convenient and reasonable recycling options, visit www.epson.com/recycle | ¹⁰ SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. | ¹¹ Expedited shipping not available in all areas. Road Service orders must be in by 3 p.m. Eastern Time for Next-Business-Day delivery.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness

Better Products for a Better FutureSM
eco.epson.com

