

CHRISTIE HS SERIES D13WU2-HS / D13HD2-HS

Auditoriums | Enterprise venues and boardrooms | Entertainment venues | Fixed installation | Education spaces
| Houses of worship | Hotels | Live events and conferences | Rental and staging | Trade shows and exhibitions

Brilliant colors at a brilliant price.

When color accuracy and affordability are key, choose the Christie® D13WU2-HS or D13HD2-HS 1DLP® laser projector. With 13,000 lumens, HD or WUXGA resolution and our Christie BoldColor™ Technology, visuals are vibrant and more true-to-life than standard laser phosphor projectors.

With built-in Christie Twist™ warping and blending, the HS Series is quick and easy to set up, on their own or as part of a multi-projector array. And with the option to add Christie Mystique® automated camera-based alignment software, you can align and recalibrate multi-projection systems in minutes. With a compact and lightweight form factor, omnidirectional capabilities, and optional rigging frame, the D13WU2-HS and D13HD2-HS are perfect options for challenging installations.



CHRISTIE®

ProSelecta

View :: Compare :: Select - www.ProSelecta.com

Technical specifications

Christie D13WU2-HS

Christie D13HD2-HS

Image	brightness (lumens)	<ul style="list-style-type: none"> • 13, 500 ISO • 12, 500 ANSI 	<ul style="list-style-type: none"> • 13, 000 ISO • 12,000 ANSI
	color wheel	• 4 segment (RGBY) - 2X or 3X speed	
	contrast (nominal)	<ul style="list-style-type: none"> • Full on/off (Christie RealBlack™ enabled): 2,000,000:1 • Dynamic contrast: 6000:1 • Full on/off (Christie RealBlack disabled): 1200:1 • ANSI 250:1 	
Display technology	type	• 1 x 0.96" DMD	
	native resolution	• 1920 x 1200 (2,304,000 pixels) (16:10)	• 1920 x 1080 (2,073,000 pixels) 16:9
Illumination	type	• Laser phosphor with Christie BoldColor™ Technology	
	performance	• 20,000 hrs to 50% brightness	
Signal Inputs	standard	<ul style="list-style-type: none"> • HDMI x 2 (HDCP 2.2) (one on side panel, one on bottom) • 3GSDI x 1 (BNC) • DVI-D x 1 (digital only) • VGA x 1 • USB x 1 (Type A) • Wi-Fi® dongle (optional) • HDBaseT (RJ45) x 1 	
	signals	<ul style="list-style-type: none"> • HDTV formats VGA through to WUXGA (1920 x 1200) • Horizontal and vertical scaling while maintaining aspect ratio, all inputs 	
	3D	<ul style="list-style-type: none"> • HDMI 1.4, HDBaseT - frame packed, top/bottom, side-by-side (up to 120Hz output); frame sequential @ 1080P up to 120Hz. • 3D sync in (BNC) - for genlocking projectors • 3D sync out (BNC) - for genlocking projectors, or controlling emitter or polarizer 	
	pixel clock	• 162 MHz	
	scan rates	• Horizontal: 15-91kHz • Vertical: 24-85Hz	
Signal outputs	monitor out (loop-through)	• 3GSDI x 1 (BNC) • HDMI x 1 (HDMI out)	
Control and networking		<ul style="list-style-type: none"> • HDBaseT (RJ45 x 1) • RJ45 x 1 (Ethernet Control over wired network connection) • RS232 x 1 • Built-in backlit keypad • IR Remote • Remote in: 3.5mm stereo female (provides serial communications and power) • Loop out available for daisy chaining • DC JACK 12VDC, 200 mA. 	
	Warping and blending	mount type	• Christie Twist™
	optional	<ul style="list-style-type: none"> • Christie Twist Premium and Twist Pro • Christie Mystique® automated camera-based alignment 	
Lenses	mount type	<ul style="list-style-type: none"> • Boresight adjustable • Motorized horizontal and vertical lens offset (memory available) • Motorized zoom and focus adjustment (memory available for full ILS lenses) 	
	lens options	• 0.38:1 UST lens • 0.84-1.02:1 zoom lens (no zoom/focus memory)	
		• 1.02-1.36:1 zoom lens (no zoom/focus memory)	
		• 1.2-1.5:1 zoom lens (full ILS) • 1.5-2.0:1 zoom lens (full ILS) • 2.0-4.0:1 zoom lens (full ILS)	
		• 4.0-7.0:1 zoom lens (full ILS)	
	offsets for 0.38:1 UST lens	<ul style="list-style-type: none"> • +100/-55% Vertical • +4/-28% Horizontal 	<ul style="list-style-type: none"> • +120%/-65% Vertical • +7%/-15% Horizontal
offsets for 0.84-1.02:1	• +108/-74% Vertical • +40/-49% Horizontal		
offsets for 1.02-1-1.36:1	• +124/-98% Vertical • +40/-49% Horizontal		
offsets for full ILS Lenses	• ±140% Vertical • ±50% Horizontal		
Accessories	standard	<ul style="list-style-type: none"> • IR remote with wired remote jack (wire not included) • AC line cord for projector • Product Safety Guide 	
	optional	<ul style="list-style-type: none"> • One Mount Extender Rod (121-125109-XX) • One Mount Rigging Kit (used with One Mount, One Mount Plus Extender Rod) (121-126100-XX) • Christie One Rigging Frame (140-113106-XX) • WiFi Dongle (133-113106-XX) • Fog Filter with Frame (003-005714-XX) • Fog Filter module (003-005715-XX) 	
Power requirements	operating voltage	• Normal mode: 120-240VAC @ 60/50 Hz with 15A fuse	
	power consumption	• Normal mode: 1050 W • Eco1 mode: 900W Eco2 mode: 600W	
	operating current	• Normal mode: 13A (100V for Japan), 10A (110V for Taiwan), 12A (100-240V), 7A (200-240V)	
	dissipation	• Normal mode: 3583 BTU/hr • Eco1 mode: 3071 BTU/hr • Eco2 mode: 2047 BTU/hr	
Audible noise		• Standard mode: 38dB(A) • Eco2 mode: 35dB(A) (2x wheel speed)	
		• Standard mode: 39dB(A) • Eco2 mode: 37dB(A) (3x wheel speed)	
Physical	size	• (L xWxH) 26.7 x 23.5 x 8.0" (677 x 596 x 203mm) w/o feet	
	shipping size	• (L xWxH) 38.0 x 31.3 x 14.4" (965 x 795 x365mm)	
	weight	• 91.52lb (41.6kg)	
	shipping weight	• 117.7lb (53.3kg)	
Operating environment	temperature	• 32-104°F (0-40°C)	
	humidity	• 10-85% non-condensing	
Regulatory		<ul style="list-style-type: none"> • This product conforms to all relevant European directives, standards, safety, health and environmental concerns • Directives: RoHS • REACH • WEEE • Contact Christie for timing of certifications: UL/CSA/IEC 60950-1 • CCC , CEL, CECP • FCC Class A • cTUVus • CE • FDA • CCC • KC • PSE • EAC • BIS • VCCI • RCM • TER • Mexico • BSMI 	
Warranty		<ul style="list-style-type: none"> • Three years parts and labor on the projector • Three years or 20,000 hours parts and labor on the illumination system¹ • Contact an authorized Christie representative for full details of our limited warranty 	

¹ Reference the Christie Standard Limited Warranty document for details.

For the most current specification information, please visit christiedigital.com

Copyright 2021 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD1915_Christie HS Series_D13_Datasheet_April 2021_EN



CHRISTIE®